TX-3000 PIONEERING HIGHPERFORMANCE LARGE-FORMAT MODEL WITH STUNNING VERSATILITY.



- Productive output speeds from the new print head design, and continuous printing option
- Supreme accuracy and peerless precision thanks to LUCIA TD ink
- Simple user operation, with dual-roll feeding available for the first time on a 36-inch model
- Brilliant colour gamut on plain media and superb performance on uncoated paper
- Straightforward control thanks to easy roll loading, touchscreen display and direct printing from USB
- Print to any network-connected TX-Series unit via the universal driver
- Neat and slender, the TX-3000 fits easily into compact office spaces
- Class-leading reliability, with unparalleled uptime and rock-solid security
- Take full advantage of weather-resistant media, perfect for CAD, GIS and outdoor Posters
- Bundled software helps to ensure smooth large-format-printing workflows

The advanced 36-inch large-format inkjet ideal for CAD, GIS and Poster printing. Engineered to deliver superb precision, efficient output, reassuring security credentials and low-cost operation.



PRODUCT RANGE



Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3000

TECHNOLOGY

Printer Type

5 Colour - 36"/914.4mm

Print Technology

Number of Nozzles

Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)

Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each

2 400 x 1200 dpi

Print Resolution Nozzle Pitch 1,200 x 2 includes Non-firing nozzle detection and

compensation system

0.02 mm

Guaranteed Minimum Line Width

Line Accuracy Ink Droplet Size Ink Capacity

Ink Type

OS Compatability

Printer Languages

Standard Interfaces

MEMORY

Standard memory **Expansion slot**

HARD DISK

PAPER HANDLING Media Width

Media Thickness Minimum Printable Length Maximum Printable Length

Maximum Media Roll

Paper Feed Method

±0.1 % or less

5 Picoliter per colour

Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y)

Sales Ink: 160ml/330ml/700ml

Pigment ink: 5 colour MBK/BK/C/M/Y

Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/ R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11

HP-GL/2, HP RTL, PDF, JPEG for details check specifications

USB B Port: Type: Built in (Hi-Speed USB)

Mode: Full Speed (12 Mbit/sec), High Speed (480

Mbit/sec), Bulk transfer

Connector Port: Series B (4 pins)

IEEE 802.3u 100base-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation

IEEE 802.3x Full Duplex

SNMP (Canon-MIB, HTTP, TCP/IP (IPv4/IPv6), ftp

Wireless LAN:

IEEE802.11n/IEEE802.11g/IEEE802.11b

128GB (Physical memory 2GB)

Roll paper: 8"/203.2mm - 36"/914.4mm Cut sheet: 8"/203.2mm - 36"/914.4mm

0.07 - 0.8mm 203.2mm

Cut Sheet: 1.6m

Borderless Printing Width

[Recommended] 515mm(JIS B2), 594mm(ISO A1)

728mm (JIS BI), 841mm (ISO AO), 10", 14", 17", 24", 36" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2)

DIMENSIONS AND WEIGHT

Physical Dimensions -(W x D x H)

Software Included

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment Noise Level (Approx.)

USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T

WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)

500GB (Encrypted)

Roll Paper: 18m (varies according to the OS and application)

Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)

(Roll Only)

, 12", 16", 20", 30", 300mm, 500mm, 600mm,

Printer unit with basket open and printer stand: 1389 x 984 x 1168 mm (Basket Open)

Weight: 105 kg (including Roll Holder) imagePROGRAF TX-Series Printer Driver Print Plug-In for Office, Quick Utility Toolbox and

PosterArtist Lite Other software available as Download from Web.

Input Power: AC 100-240 V (50-60 Hz)

Power consumption (using wired LAN): 105 W or less

At sleep mode (using wired LAN): 3.6 W or less At sleep mode (using whed LAN), 3.6 W or less <EU only - data for ErP Lot 26> At the power off: 0.3 W or less

Default setting for the time to enter the Sleep mode:

<EU only - data for ErP Lot 26>

15 - 30°C, 10 - 80 % (Condensation free)

Operation : 51dB(A) or less (Plain paper, line drawing, standard mode) Stand by : 35dB(A) or less (Measured on ISO7779 standard)

Regulations

Europe: CE mark Russia: EAC, Other Countries: CB certification ENERGY STAR (WW), RoHS directive, IT ECO

Declaration (Europe), WEEE

WHAT'S INCLUDED What's in the Box?

Enviroment Certificates

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3 Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet

Roll Unit: RU-32

Stacker: SS-31 2/3" Roll Holder: RH2-34

CONSUMABLES

User Replaceable Items

Print Head: PF-06 Ink Tanks: PFI-110 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

Disclaimer

OPTIONS Optional Items

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and R: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.









Canon Inc.

Canon Europe canon-europe.com

English edition © Canon Europa N.V.,2017

Explore. Inspire. Improve.